

HIGH-PRESSURE JETTING MACHINE

TO CLEAN AND UNBLOCK SEWERS AND DRAINS QUICKLY AND EFFECTIVELY

PYTHON very functional device with small dimensions, designed for hydrodynamic cleaning of sanitary, rainwater and industrial pipes with a maximum diameter of up to 500 mm (depending on the version). The device has been developed and manufactured by *KanRo Ltd*[®] based on many years of experience in the sale and service of high -pressure cleaning equipment.



PYTHON 3.0 high-pressure jetting machine can be mounted on standard 1- and 2-axis transport trailers. In addition, trailers can be equipped with a factory frame with a tarpaulin or a plastic housing. It can also be fitted to commercial van vehicles. Everywhere where big cleaning cars cannot be reached, PYTHON 3.0 will be perfect. The PYTHON 3.0 device has been equipped with a reliable high-pressure pump from the renowned European manufacturer UDOR from Italy. The pump with ceramic plungers, thanks to which it is possible to work with the device using hot water. It can be also operated by one person from panel control or also with remote radio control.

AREAS OF APPLICATION

- ✓ cleaning the sewage network
- ✓ cleaning rainwater drainage
- ✓ cleaning the water supply network
- ✓ cleaning drainage pipes
- ✓ pressure washer
- ✓ watering greenery



PYTHON 3.0 - SPECIFICATION

ENGINE	BRIGGS&STRATTON 37 HP VANGUARD petrol engine with an electric starter	
PUMP	UDOR triplex plunger pump fitted with ceramic plungers; pressure regulator and manometer	
PUMP EFFICIENCY	150 bar working pressure, 75 l/min. flow rate	200 bar working pressure, 60 l/min. flow rate
WATER TANK	with a capacity of 650 l (optionally 800 l, 1000 l),	
PANEL CONTROL	panel control located in the device	
REMOTE RADIO CONTROL	Optional. 7-channel remote radio control: engine start/stop, motor speed plus/minus, pump start/stop, safety switch	
HIGH-PRESSURE HOSE	hose 60/80 m long, inside diameter NW 13 mm, coupling ½"	
HIGH-PRESSURE HOSE REEL	manual hose reel, optional - hose reel with hydraulic drive with smooth, stepless speed control in both directions and the free-running position with the rotating union and three-way valve, hose reel is equipped with a guide for even placement of the hose	
FILLING HOSE	manual reel with filling hose length 50 m, NW 19 mm	
APPLICATION RANGE	pipes diameter max 500 mm	
STANDARD EQUIPMENT	<ul style="list-style-type: none"> ✓ spraygun and lanc 700 mm ✓ digital hour meter ✓ standard nozzle open ✓ standard nozzle blind ✓ rinsing nozzle "GRENADA" ✓ piercing nozzle "QUATTRO" ✓ protection against running dry ✓ protection against working without oil ✓ winter circulation ✓ user manual, CE certificate 	

