

## 14.00R20 S02 PISTA HD



|                                |                                       |                     |     |
|--------------------------------|---------------------------------------|---------------------|-----|
| Brand                          | Prometeon                             |                     |     |
| Tread pattern                  | S02 PISTA HD                          |                     | M+S |
| Size (*)                       | 14.00R20 POR                          | TL (TT)             |     |
| Load index and speed code (*)  | 168/166K                              |                     |     |
| ECE 54 HOMOLOGATION N.         | E4                                    | 0054991             |     |
| ECE117 HOMOLOGATION N.         | Exempted as P.O.R Tyre                |                     |     |
| Ecolabel                       |                                       |                     |     |
| Application   Axle             | Special Use                           | All Position        |     |
| Weight [kg]                    | 106,0                                 | (± 3.0%)            |     |
| Section width [mm] (*) (+)     | 376                                   | (± 1.5%)            |     |
| Outer diameter [mm] (*)        | 1240                                  | (± 0.5%)            |     |
| Static loaded radius [mm] (*)  | 565                                   | (± 1.0%)            |     |
| Rolling circumference [mm] (*) | 3782                                  | (± 1.0%)            |     |
| Tread width [mm]               | 315                                   |                     |     |
| Tread depth [mm]               | 20 central groove, 23 shoulder groove |                     |     |
| Rims                           | 10,00                                 | [10.00V 10.00W 9.0] |     |
| Minimum dual spacing [mm]      | 439                                   | [439 428]           |     |
| MAX LOAD PER AXLE              |                                       |                     |     |
| Load index and speed code (*)  | 168/166K                              | -                   |     |
| Single / dual fitment [kg] (*) | 11200/21200                           | -                   |     |
| Nominal pressure [bar] (*)     | 8,50                                  | -                   |     |
| Max speed [km/h]               | 110                                   | -                   |     |

(\*) ECE54 STANDARD

(+) ON UNDERLINED RIM

### ALL RIGHTS RESERVED

Any reproduction prohibited without permission of:

**Prometon Tyre Group S.r.l**

Prometeon Tyre Group S.r.l. - O.E. Assistance

**PROMETEON INTERNAL USE**